


EIKI LC-SVGA860

SVGA/MAC16 Resolution Portable Data/Video Projector

KEY FEATURES:

- Projects true SVGA/MAC16: 800x600 pixels in SVGA, 832x624 pixels in MAC16.
- 700 ANSI Lumens light output at 85%+ uniformity for brilliant images -- even in normal room light!
- Compact 14.3 Lb. design with built-in carrying handle fits easily into airline overhead compartments.
- Displays higher resolutions compressed or panned, and lower resolutions normal or expanded.
- Projects up to a 400" diagonal picture from distances up to 75.2'.
- Wireless Remote/Mouse controls both the projector and the computer, from anywhere in the room.



OTHER IMPORTANT FEATURES:

- UHP (Ultra High Performance) Long Life 120 Watt lamp.
- Multi Format Video: NTSC, PAL, SECAM, NTSC 4.43 Video
- International Power: 100- 120 / 200- 240 V AC, 50/60 Hz.
- Included Accessories: VGA Cable, MAC Adaptor, Owner's Manual, Dust Cover, Remote Control, AA batteries x 2, AC Power Cord, Mouse cables for PS/2, Serial Port, ADB Port, Eiki Pocket Point.
- Optional Accessories: Replacement Lamp, Soft Travel Case with wheels and telescoping handle. Soft Carry Bag. Hard Shipping Case. Ceiling Mount, Post and Plate. MAC Monitor Cable. Other/Additional Input Cables.

LC-SVGA860 SPECIFICATIONS:

Screen Brightness	700 ANSI Lumens
Illumination Uniformity	85%
Size of Color Palette	16.7 Million
Contrast Ratio	250 :1 (ANSI 100:1)
Horizontal Resolution	750 TV Lines
Projection Lamp	120 Watt, UHP
Estimated Lamp Life	4,000 Hours
RGB Separation	Polarized Beam Splitter & Polarization Capture
RGB Distribution	Dichroic Mirror & X-Prism System
Light Optimization	Integrator MicroLens (Pair)
Imaging System	1.3" Polysilicon TFT Panels x 3
Screen Pixels	800X600 SVGA, 832X624 MAC16
Total Pixels	480,000X3 = 1,440,000 SVGA, 519,168X3 = 1,557,504 MAC16
Lens Type	1:1.6 Power Zoom and Focus
Lens Speed & Focal Length	f 2.5-3.2; 1.85-2.96 in (47-75mm)
Lens Protection	Auto Lens Retract and Cover
Image Diagonal	20"~400"
Image Width	1.3'~26.7' (0.4m ~ 8.1m)
Throw Distance	3.6'~75.2' (1.1m ~22.9m)
Width-to-Throw Factor	1.75 Max@WA - 2.80 Max @TP
Front Elevation:	Up to 6.5 Degrees
Image Offset	9.25 Degrees Up, Ratio (T:B) 8:1
Scanning	H Sync. 15-80kHz; V Sync. 50-100Hz
Image Orientation	Normal, Reversed, Inverted
Local Control	Full Function
Remote Control	IR Projector & Mouse Control

SPECIFICATIONS (cont.)

Mouse Control Ports	8 Pin DIN x 2
RS-232 Control Ports	8 Pin DIN (on Mouse Control Port #2) x 1
Computer Standards	SVGA, VGA, MAC16, MAC13
Computer Other	XGA& MAC19, DRIT Compressed or Panned
Computer Formats	Normal, or Expanded (VGA and MAC13)
Computer Channels	2
Computer Inputs	(VGA Cable & MAC Adaptor to) HDB 15 x 2
Computer Monitor Out	HDB 15 x 1
Computer Audio Input	Stereo: MiniStereo x 2
Video Formats	Normal (4:3); Wide (16:9)
Video Standards	NTSC / PAL / SECAM / NTSC 4.43
Video Channels	1
Video Inputs	Composite: RCAx 1, Y/C: S-Video x 1
Video Output	RCAx 1
Video Audio Input	Stereo: RCAx 2 (L&R)
Audio Amplifier	Stereo: 2 Watts RMS each (L&R), 3 Watt peak
Built-in Speakers	Stereo: 1.57" x 2.75" (4cm x 7cm) x 2
External Speaker Output:	Stereo: Stereo MiniJack x 1
Fan Noise	less than 45dB
Audio Monitor	Stereo: Mini Stereo x 1
Size (HxWxD)	6.3" x 10.3" x 15.9" (15.8 x 26.0 x 40.4 cm)
Weight	14.3 Lb. (6.5 kg)
Power Requirements	100-120V / 200-240V AC, 50/60 Hz
Power Consumption	200 Watts
Power Cord	10' (3M) Type 3, Detachable
Safety Compliances	UL Listed
Warranty - Projector	3 Years (Parts & Labor to Correct Defects)
Warranty - Lamp	1 Year (Replacement of Failed Lamp)

EIKI

A-Key to better communications.

Specifications subject to change without notice.

©1998 EIKI International, Inc. Printed in the USA. 2/3/98

Eiki International, Inc., 26794 Vista Terrace Dr., Lake Forest, CA 92630 Phone: 800-242-3454; Fax: 800-457-3454, E-mail: eikiusa@ibm.net
EIKI CANADA, 17036 Highway 12, P.O. Box 156, Midland, ON L4R 4K8 Tel: 800-563-3454, Fax: 800-567-4069 E-mail: eikicda@eiki.ca
Visit our World Wide Web site: <http://www.eiki.ca>